



WP1-CH1-125, WP1-CH2-100 and WS-C-H Mobile

## COMPLETE MOBILE SYSTEM WITH HIGH WATER REMOVAL

The GreenOil mobile system is used for mainte- are removed. The oil is then transferred to the nance or emergency filtration of EAL bio, lubri- coalescher element, which effectively removes cation, hydraulic and gear. The system removes water in the oil. The oil then returns to the free and emulsified water and particles, varnish system. and oxidation residues in the system.

## **Functions**

The system comprises of a preheater, pump and motor unit together with a GreenOil filter and a coalescher system.

Oil passes through the preheater to increase the oil temperature. The pump continuously feeds the oil through the filter, where particles

All particle filtration is performed using the GreenOil range of filters. This results in having the cleanest possible oil ready for use.

Filter insert is replaced without the use of tools, oil spill or physical contact with the oil.

ldeal when water ingress becomes an issue and needs removing.

## **KEY FEATURES**

- Integrated oil filter and water separator.
- Effective and quick water removal.
- Easy and quick filter change without oil
- No tools required for filter replacement.
- No physical contact with oil when replacing filter insert.
- A low maintenance system with many benefits.

TECHNICAL DATA	WP1-CH1-125 Mobile	WP1-CH2-100 Mobile	WS-C-H Mobile
Filtered Oil Flow [l/h]	100-125	100-120	-
Water removal [l/day]	≤ 4	≤ 10	≤ 10
Oil Pressure In, max. [Bar]	1	1	1
Oil Suction Height [m]	6	б	б
Viscosity [cSt]	0-460	0-460	0-460
Power Supply [VAC - Hz]	230/3x440-50/60	230/3x440-50/60	230/3x440-50/60
Power Consumption [W]	125 +1600	125 +1600	1600
Connections ["RG] (BSP)	1/2	1/2	1/2
Dimensions H x W x D [mm]	1160 x 550 x 560	1160 x 550 x 520	1160 x 550 x 520
We <b>ight</b> [kg]	24	51	32
Materials	AISI 304 Stainless	AISI 304 Stainless	AISI 304 Stainless
Filter canister [liter]	1 x 8	1 x 8	None
Preheater	Standard	Standard	Standard
Hydraulic hoses	2 x 5 m 1/2"	2 x 5 m 1/2"	2 x 5 m 1/2"